



# Hot Melt Adhesive Roll Coater (Glue Wheel) - Models GW 36 & 48

Capable • Affordable • Maintainable



Front and back views of Model GW 36



Roll Coater adjustable controls

### System Features:

- Fast start up time
- Extra-large capacity tank for continuous operation
- Totally self-contained and portable
- Quickly removable top roller assembly
- Safety emergency stop switch and safety guarding
- Drive overload limit clutch
- High limit over-temp thermostat
- Adjustable heated blade to control adhesive thickness
- Digital electronic temperature control
- DC variable speed drive

### Technical Specifications:

Model	GW 24	GW 36	GW 48
Maximum Width	24 (609)	36 (914)	48 (1219)
Thickness Range	6 (152)		
Work Table	24 x 24	24 x 36	36 x 53.6
Watts (kW)	9	13.5	28.25
Electrical	240 volt, 3 phase		
Maximum Temp. (°F)	550		
Velocity (ft./min)	0 to 94		

Dimensions shown in inches (mm)

Due to our continuous improvement program, specifications and options are subject to change without notice.



Ttarp Co. • 338 Scajaquada Street, Buffalo, NY 14211  
 Toll Free: 800-871-7596 • Phone: 716-894-5613  
 E-mail: joe@ttarp.com • www.Ttarp.com